State "Transmittal Checklist" to Assist in Targeting Municipal and Industrial Individual NPDES Draft Permits for Review

Part I. State Draft Permit Submission Checklist

In accordance with the MOA established between the Commonwealth of Virginia and the United States Environmental Protection Agency, Region III, the Commonwealth submits the following draft National Pollutant Discharge Elimination System (NPDES) permit for Agency review and concurrence.

Facility Name: Chesapeake Energy Center						
NPDES Permit Number:	VA0004081					
Permit Writer Name:	Melinda Woodruf	f				
Date:	October 28, 2011					
Major [x]	Minor[]	Industrial [ێֱ]	Municipal []			
I.A. Draft Permit Package Submittal Includes:			Yes	No	N/A	
1. Permit Application?	1. Permit Application?					
·	Complete Draft Permit (for renewal or first time permit – entire permit, including boilerplate information)?					
3. Copy of Public Notice?				Х		
4. Complete Fact Sheet?	4. Complete Fact Sheet? X					
5. A Priority Pollutant Scree	ning to determine p	arameters of concern?	Х	· · · · · · · · · · · · · · · · · · ·		
6. A Reasonable Potential a	. A Reasonable Potential analysis showing calculated WQBELs? X					
7. Dissolved Oxygen calcula	'. Dissolved Oxygen calculations?					
8. Whole Effluent Toxicity Te	est summary and ar	nalysis?	Х			
9. Permit Rating Sheet for n	ew or modified indu	strial facilities?			Х	
I.B. Pe	rmit/Facility Ch	naracteristics	Yes	No	N/A	
1. Is this a new, or currently	unpermitted facility	?		Х		
	Are all permissible outfalls (including combined sewer overflow points, non- process water and storm water) from the facility properly identified and authorized in the permit?					
Does the fact sheet or pe treatment process?	Does the fact sheet or permit contain a description of the wastewater					
I.B. Permit	/Facility Charac	cteristics - cont.	Yes	No	N/A	
	Does the review of PCS/DMR data for at least the last 3 years indicate significant non-compliance with the existing permit?			Х		
5. Has there been any change in streamflow characteristics since the last permit was developed?						

6 Dogg the narmitallow the discharge of according to the discharge of		l	[
6. Does the permit allow the discharge of new or increased loadings of any pollutants?		Х	
7. Does the fact sheet or permit provide a description of the receiving water body(s) to which the facility discharges, including information on low/critical flow conditions and designated/existing uses?	Х		
8. Does the facility discharge to a 303(d) listed water?	Х		
a. Has a TMDL been developed and approved by EPA for the impaired water?	Х		
b. Does the record indicate that the TMDL development is on the State priority list and will most likely be developed within the life of the permit?			х
c. Does the facility discharge a pollutant of concern identified in the TMDL or 303(d) listed water?	Х		
9. Have any limits been removed, or are any limits less stringent, than those in the current permit?		х	
10. Does the permit authorize discharges of storm water?	Х		
11. Has the facility substantially enlarged or altered its operation or substantially increased its flow or production?		х	
12. Are there any production-based, technology-based effluent limits in the permit?	Х		
13. Do any water quality-based effluent limit calculations differ from the State's standard policies or procedures?		Х	
14. Are any WQBELs based on an interpretation of narrative criteria?	Х		
15. Does the permit incorporate any variances or other exceptions to the State's standards or regulations?		Х	
16. Does the permit contain a compliance schedule for any limit or condition?		Х	
17. Is there a potential impact to endangered/threatened species or their habitat by the facility's discharge(s)?		х	
18. Have impacts from the discharge(s) at downstream potable water supplies been evaluated?			х
19. Is there any indication that there is significant public interest in the permit action proposed for this facility?		х	
20. Have previous permit, application, and fact sheet been examined?	Х		

Part II. NPDES Draft Permit Checklist

Region III NPDES Permit Quality Checklist – for POTWs **NA**

(To be completed and included in the record only for POTWs)

	II.A. Permit Cover Page/Administration	Yes	No	N/A
	Does the fact sheet or permit describe the physical location of the facility, including latitude and longitude (not necessarily on permit cover page)?			
	Does the permit contain specific authorization-to-discharge information (from where to where, by whom)?		r	
	II.B. Effluent Limits - General Elements	Yes	No	N/A
(Does the fact sheet describe the basis of final limits in the permit (e.g., that a comparison of technology and water quality-based limits was performed, and the most stringent limit selected)?			
	Does the fact sheet discuss whether "antibacksliding" provisions were met for any limits that are less stringent than those in the previous NPDES permit?			
II.C.	. Technology-Based Effluent Limits (POTWs)	Yes	No	N/A
	Does the permit contain numeric limits for <u>ALL</u> of the following: BOD (or alternative, e.g., CBOD, COD, TOC), TSS, and pH?			
6	Does the permit require at least 85% removal for BOD (or BOD alternative) and TSS (or 65% for equivalent to secondary) consistent with 40 CFR Part 133?		-	
á	a. If no, does the record indicate that application of WQBELs, or some other means, results in more stringent requirements than 85% removal or that an exception consistent with 40 CFR 133.103 has been approved?	2		
	Are technology-based permit limits expressed in the appropriate units of measure (e.g., concentration, mass, SU)?			
1	Are permit limits for BOD and TSS expressed in terms of both long term (e.g., average monthly) and short term (e.g., average weekly) limits?			
	Are any concentration limitations in the permit less stringent than the secondary treatment requirements (30 mg/l BOD5 and TSS for a 30-day average and 45 mg/l BOD5 and TSS for a 7-day average)?			
8	a. If yes, does the record provide a justification (e.g., waste stabilization pond, trickling filter, etc.) for the alternate limitations?			
	II.D. Water Quality-Based Effluent Limits	Yes	No	N/A
	Does the permit include appropriate limitations consistent with 40 CFR 122.44(d) covering State narrative and numeric criteria for water quality?			
•	Does the fact sheet indicate that any WQBELs were derived from a completed and EPA approved TMDL?			
II.D.	. Water Quality-Based Effluent Limits – cont.	Yes	No	N/A
3.	Does the fact sheet provide effluent characteristics for each outfall?		,	AND

4.	Does the fact sheet document that a "reasonable potential" evaluation was performed?			
	a. If yes, does the fact sheet indicate that the "reasonable potential" evaluation was performed in accordance with the State's approved procedures?			
	 Does the fact sheet describe the basis for allowing or disallowing in-stream dilution or a mixing zone? 			
	c. Does the fact sheet present WLA calculation procedures for all pollutants that were found to have "reasonable potential"?			
	d. Does the fact sheet indicate that the "reasonable potential" and WLA calculations accounted for contributions from upstream sources (i.e., do calculations include ambient/background concentrations)?			
	e. Does the permit contain numeric effluent limits for all pollutants for which "reasonable potential" was determined?			
5.	Are all final WQBELs in the permit consistent with the justification and/or documentation provided in the fact sheet?			
6.	For all final WQBELs, are BOTH long-term AND short-term effluent limits established?			
7.	Are WQBELs expressed in the permit using appropriate units of measure (e.g., mass, concentration)?			
8.	Does the record indicate that an "antidegradation" review was performed in accordance with the State's approved antidegradation policy?			
	II.E. Monitoring and Reporting Requirements	Yes	No	N/A
1.	Does the permit require at least annual monitoring for all limited parameters and other monitoring as required by State and Federal regulations?			Provide the control of the control o
	a. If no, does the fact sheet indicate that the facility applied for and was granted a monitoring waiver, AND, does the permit specifically incorporate this waiver?			
	Does the permit identify the physical location where monitoring is to be			And the second of the second o
2.	performed for each outfall?			Sampa Arthur Lings
 3. 	performed for each outfall? Does the permit require at least annual influent monitoring for BOD (or BOD alternative) and TSS to assess compliance with applicable percent removal requirements?			
3.	Does the permit require at least annual influent monitoring for BOD (or BOD alternative) and TSS to assess compliance with applicable percent removal			
3.	Does the permit require at least annual influent monitoring for BOD (or BOD alternative) and TSS to assess compliance with applicable percent removal requirements?	Yes	No	N/A
	Does the permit require at least annual influent monitoring for BOD (or BOD alternative) and TSS to assess compliance with applicable percent removal requirements? Does the permit require testing for Whole Effluent Toxicity?	Yes	No	N/A
3.4.1.	Does the permit require at least annual influent monitoring for BOD (or BOD alternative) and TSS to assess compliance with applicable percent removal requirements? Does the permit require testing for Whole Effluent Toxicity? II.F. Special Conditions	Yes	No	N/A
3.4.1.2.	Does the permit require at least annual influent monitoring for BOD (or BOD alternative) and TSS to assess compliance with applicable percent removal requirements? Does the permit require testing for Whole Effluent Toxicity? II.F. Special Conditions Does the permit include appropriate biosolids use/disposal requirements?	Yes	No	
3.4.1.2.	Does the permit require at least annual influent monitoring for BOD (or BOD alternative) and TSS to assess compliance with applicable percent removal requirements? Does the permit require testing for Whole Effluent Toxicity? II.F. Special Conditions Does the permit include appropriate biosolids use/disposal requirements? Does the permit include appropriate storm water program requirements?			N/A

5.	5. Does the permit allow/authorize discharge of sanitary sewage from points other than the POTW outfall(s) or CSO outfalls [i.e., Sanitary Sewer Overflows (SSOs) or treatment plant bypasses]?					
6.	Does the permit authorize discharges from Combined Sewer Overflows (CSOs)?					
	a. Does the permit require implementation of the "Nine Minimum Controls"?					
	b. Does the permit require development and implementation of a "Long Term Control Plan"?					
	c. Does the permit require mo	nitoring and reporting for CSO ev	rents?			
7.	7. Does the permit include appropriate Pretreatment Program requirements?					
	II.G.	Standard Conditions		Yes	No	N/A
1.	Does the permit contain all 40 equivalent (or more stringent)	O CFR 122.41 standard condition conditions?	s or the State			
Lis	st of Standard Conditions – 4	0 CFR 122.41				
Du Ne Du Pro	Duty to comply Duty to reapply Need to halt or reduce activity not a defense Duty to mitigate Proper O & M Property rights Duty to provide information Inspections and entry Monitoring and records Signatory requirement Bypass Permit actions Property rights Duty to provide information Inspections and entry Monitoring and records Signatory requirement Bypass Upset Reporting Requirements Planned change Anticipated noncompliance Transfers Monitoring reports Compliance schedules 24-Hour reporting Other non-compliance					nce
2.	Does the permit contain the additional standard condition (or the State equivalent or more stringent conditions) for POTWs regarding notification of new introduction of pollutants and new industrial users [40 CFR 122.42(b)]?					and the second s

Part II. NPDES Draft Permit Checklist

Region III NPDES Permit Quality Review Checklist – For Non-Municipals (To be completed and included in the record for <u>all</u> non-POTWs)

	II.A. Permit Cover Page/Administration	Yes	No	N/A
1.	Does the fact sheet or permit describe the physical location of the facility, including latitude and longitude (not necessarily on permit cover page)?	Х		
2.	Does the permit contain specific authorization-to-discharge information (from where to where, by whom)?	Х		

	II.B. Effluent Limits - General Elements	Yes	No	N/A	
1.	Does the fact sheet describe the basis of final limits in the permit (e.g., that a comparison of technology and water quality-based limits was performed, and the most stringent limit selected)?	х			
Does the fact sheet discuss whether "antibacksliding" provisions were met for any limits that are less stringent than those in the previous NPDES permit?			Х		

II.C	C. Technology-Based Effluent Limits (Effluent Guidelines & BPJ)	Yes	No	N/A
1.	Is the facility subject to a national effluent limitations guideline (ELG)?	Х		
	a. If yes, does the record adequately document the categorization process, including an evaluation of whether the facility is a new source or an existing source?	х		
	b. If no, does the record indicate that a technology-based analysis based on Best Professional Judgement (BPJ) was used for all pollutants of concern discharged at treatable concentrations?			Х
2.	For all limits developed based on BPJ, does the record indicate that the limits are consistent with the criteria established at 40 CFR 125.3(d)?	Х		
3.	Does the fact sheet adequately document the calculations used to develop both ELG and /or BPJ technology-based effluent limits?	Х		
4.	For all limits that are based on production or flow, does the record indicate that the calculations are based on a "reasonable measure of ACTUAL production" for the facility (not design)?	Х		
5.	Does the permit contain "tiered" limits that reflect projected increases in production or flow?		х	
	a. If yes, does the permit require the facility to notify the permitting authority when alternate levels of production or flow are attained?			x
6.	Are technology-based permit limits expressed in appropriate units of measure (e.g., concentration, mass, SU)?	х		

II.C. Technology-Based Effluent Limits (Effluent Guidelines & BPJ) – cont.	Yes	No	N/A
7. Are all technology-based limits expressed in terms of both maximum daily, weekly average, and/or monthly average limits?	Х		
8. Are any final limits less stringent than required by applicable effluent limitations guidelines or BPJ?		Х	

	II.D. Water Quality-Based Effluent Limits	Yes	No	N/A
1.	Does the permit include appropriate limitations consistent with 40 CFR 122.44(d) covering State narrative and numeric criteria for water quality?	Х		
2.	Does the record indicate that any WQBELs were derived from a completed and EPA approved TMDL?		Х	
3.	Does the fact sheet provide effluent characteristics for each outfall?	Х		
4.	Does the fact sheet document that a "reasonable potential" evaluation was performed?	Х		
	a. If yes, does the fact sheet indicate that the "reasonable potential" evaluation was performed in accordance with the State's approved procedures?	Х	· · · · ·	
	 b. Does the fact sheet describe the basis for allowing or disallowing in-stream dilution or a mixing zone? 	х		
	c. Does the fact sheet present WLA calculation procedures for all pollutants that were found to have "reasonable potential"?	Х		
	d. Does the fact sheet indicate that the "reasonable potential" and WLA calculations accounted for contributions from upstream sources (i.e., do calculations include ambient/background concentrations where data are available)?			х
	e. Does the permit contain numeric effluent limits for all pollutants for which "reasonable potential" was determined?	х		
5.	Are all final WQBELs in the permit consistent with the justification and/or documentation provided in the fact sheet?	Х		
6.	For all final WQBELs, are BOTH long-term (e.g., average monthly) AND short-term (e.g., maximum daily, weekly average, instantaneous) effluent limits established?	Х	-	
7.	Are WQBELs expressed in the permit using appropriate units of measure (e.g., mass, concentration)?	Х		
8.	Does the fact sheet indicate that an "antidegradation" review was performed in accordance with the State's approved antidegradation policy?	Х		

*4

	II.E. Monitori	ng and Reporting Requirement	<u>cs</u>	Yes	No	N/A
1.	Does the permit require at least	st annual monitoring for all limited	parameters?	Х		
		licate that the facility applied for a , AND, does the permit specificall				
2.	Does the permit identify the preformed for each outfall?	ysical location where monitoring	is to be	х		
3.	Does the permit require testing the State's standard practices?	g for Whole Effluent Toxicity in acc	cordance with	х		
	II.F.	Special Conditions		Yes	No	N/A
1.	Does the permit require develor Management Practices (BMP)	opment and implementation of a Epplan or site-specific BMPs?	Best	х		
	a. If yes, does the permit adequately incorporate and require compliance with the BMPs?					Eller ha new fig. I constitution for the second of the sec
2.	If the permit contains compliance schedule(s), are they consistent with statutory and regulatory deadlines and requirements?					Х
3.	3. Are other special conditions (e.g., ambient sampling, mixing studies, TIE/TRE, BMPs, special studies) consistent with CWA and NPDES regulations?			х		
	II.G.	Standard Conditions		Yes	No	N/A
1.	Does the permit contain all 40 equivalent (or more stringent)	CFR 122.41 standard conditions conditions?	or the State	Х		
Lis	st of Standard Conditions – 40) CFR 122.41				***************************************
Duty to comply Duty to reapply Need to halt or reduce activity not a defense Duty to mitigate Proper O & M Property rights Duty to provide information Inspections and entry Monitoring and records Signatory requirement Bypass Permit actions Property rights Duty to provide information Planned change Anticipated non- Transfers Monitoring repo Compliance sch 24-Hour reportir Other non-comp				complia ts edules	nce	
2.	Does the permit contain the additional standard condition (or the State equivalent or more stringent conditions) for existing non-municipal dischargers X regarding pollutant notification levels [40 CFR 122.42(a)]?					

Part III. Signature Page

Based on a review of the data and other information submitted by the permit applicant, and the draft permit and other administrative records generated by the Department/Division and/or made available to the Department/Division, the information provided on this checklist is accurate and complete, to the best of my knowledge.

Name Melinda Woodruff

Title Environmental Engineer Senior

Signature November 15, 2011

VPDES PERMIT PROGRAM FACT SHEET FILE NO: 726

This document gives pertinent information concerning the VPDES Permit listed below. This permit is being processed as a ${\tt MAJOR\ INDUSTRIAL\ }$ permit.

L .	PERMIT NO.: VA0004081	EXPIRATION DATE: January 23, 2012
2.	FACILITY NAME AND LOCAL MAILING	FACILITY LOCATION ADDRESS (IF DIFFERENT)
	Virginia Electric and Power Company Dominion-Chesapeake Energy Center 5000 Dominion Blvd. Glenn Allen, VA 23060	2701 Vepco Street Chesapeake, VA 23320
	CONTACT AT FACILITY: NAME: Cathy Taylor TITLE: Director, Electric Environment Services PHONE: (804)273-2929 EMAIL:	CONTACT AT LOCATION ADDRESS NAME: Paul Dickson al TITLE: PHONE: () EMAIL:
3.	OWNER CONTACT: (TO RECEIVE PERMIT) NAME: Mr. C. D. Holley TITLE: VP-Fossil & Hydro System Opera COMPANY NAME: ADDRESS:	CONSULTANT CONTACT: NAME: tions FIRM NAME: ADDRESS:
	PHONE: () EMAIL:	PHONE: () EMAIL:
4.	PERMIT DRAFTED BY: DEQ, Water Permit	s, Regional Office
	Permit Writer(s): Melinda Woodruff Reviewed By: Mark Sauer	Date(s): 09/23/2011 Date(s): u/zz-z3/u
5.	PERMIT ACTION:	
	() Issuance (x) Reissuance () I () Board Modification () Change of	Revoke & Reissue () Owner Modification f Ownership/Name [Effective Date:]

6. SUMMARY OF SPECIFIC ATTACHMENTS LABELED AS:

Attachment 1 Attachment 2 Attachment 3 Attachment 4	Site Inspection Report/Memorandum Discharge Location/Topographic Map Schematic/Plans & Specs/Site Map/Water Balance TABLE I - Discharge/Outfall Description
Attachment 5	TABLE II - Effluent Monitoring/Limitations
Attachment 6	Effluent Limitations/Monitoring Rationale/Suitable Data/Antidegradation/Antibacksliding
Attachment 7	Special Conditions Rationale
Attachment 8	Toxics Monitoring/Toxics Reduction/WET Limit Rationale
Attachment 9	Material Stored
Attachment 10	Receiving Waters Info./Tier Determination/STORET Data/Stream Modeling
Attachment 11	303(d) Listed Segments
Attachment 12	TABLE III(a) and TABLE III(b) - Change Sheets
Attachment 13	NPDES Industrial Permit Rating Worksheet and EPA Permit Checklist
Attachment 14	Chronology Sheet
Attachment 15	Public Participation

APPLICATION COMPLETE: September 20, 2011

(x) Existing Discharge (x) Effluent Limited () Proposed Discharge (x) Water Quality Limited () Municipal () WET Limit SIC Code(s) () Interim Limits in Permit (x) Industrial () Interim Limits in Other Document SIC Code(s) 4911 () Compliance Schedule Required () POTW () Site Specific WQ Criteria () PVOTW () Variance to WO Standards (x) Private () Water Effects Ratio () Federal (x) Discharge to 303(d) Listed Segment () State (x) Toxics Management Program Required () Publicly-Owned Industrial () Toxics Reduction Evaluation (x) Storm Water Management Plan () Pretreatment Program Required () Possible Interstate Effect () CBP Significant Dischargers List 8. RECEIVING WATERS CLASSIFICATION: River basin information. Outfall No(s): 001 (incl.101), 002 (incl. 201, 206), 013, 015, 018, 021 Receiving Stream: Deep Creek to the southern Branch of the Elizabeth River River Mile: see attachment 10 Basin: James River (Lower) Subbasin: NA Section: 1d Class: TΤ Special Standard(s): a, z Tidal: YES 7-Day/10-Year Low Flow: NA 1-Day/10-Year Low Flow: NA 30-Day/5-Year Low Flow: NA Harmonic Mean Flow: Outfall No(s): 003 (incl. 301), 004, 005, 007, 008, 009, 010, 011, 012, 016, 017, 019, 020, 030, 031 Receiving Stream: Southern Branch of the Elizabeth River River Mile: see attachment 10 Basin: James River (Lower) Subbasin: NA Section: 1d Class: TT Special Standard(s): a, z Tidal: YES 7-Day/10-Year Low Flow: NA 1-Day/10-Year Low Flow: NA 30-Day/5-Year Low Flow: NA Harmonic Mean Flow: NA 9. **FACILITY DESCRIPTION:** Describe the type facility from which the discharges originate.

EXISTING industrial discharge resulting from the generation of electricity with

() No (X) Yes

Class: III

steam produced by the combustion of fossil fuels

LICENSED OPERATOR REQUIREMENTS:

PERMIT CHARACTERIZATION: (Check as many as appropriate)

7.

10.

12.	SITE INSPECTION DATE: September 15, 2011 REPORT DATE: October 18, 2011
	Performed By: Steve Long, Water Compliance
	SEE ATTACHMENT 1
13.	DISCHARGE(S) LOCATION DESCRIPTION: Provide USGS Topo which indicates the discharge location, significant (large) discharger(s) to the receiving stream, water intakes, and other items of interest.
	Name of Topo: Norfolk South Quadrant No.: 35D SEE ATTACHMENT 2
14.	ATTACH A SCHEMATIC OF THE WASTEWATER TREATMENT SYSTEM(S) [IND. & MUN.]. FOR INDUSTRIAL FACILITIES, PROVIDE A GENERAL DESCRIPTION OF THE PRODUCTION CYCLE(S) AND ACTIVITIES. FOR MUNICIPAL FACILITIES, PROVIDE A GENERAL DESCRIPTION OF THE TREATMENT PROVIDED.
	SEE ATTACHMENT 3 (CAN ALSO REFERENCE TABLE I)
15.	DISCHARGE DESCRIPTION: Describe each discharge originating from this facility.
	SEE TABLE I (OR CAN SUBSTITUTE PAGE 2C) - SEE ATTACHMENT 4
16.	COMBINED TOTAL FLOW:
	TOTAL: 521 MGD (for public notice)
	PROCESS FLOW: 519 (001) 1.37 (002) MGD (IND.)
	NONPROCESS/RAINFALL DEPENDENT FLOW: 0.19 (Est.)
17.	STATUTORY OR REGULATORY BASIS FOR EFFLUENT LIMITATIONS AND SPECIAL CONDITIONS: (Check all which are appropriate)
	X State Water Control Law X Clean Water Act X VPDES Permit Regulation (9 VAC 25-31-10 et seq.) X EPA NPDES Regulation (Federal Register) X EPA Effluent Guidelines (40 CFR 133 or 400 - 471) X Water Quality Standards (9 VAC 25-260-5 et seq.) Wasteload Allocation from a TMDL or River Basin Plan
18.	EFFLUENT LIMITATIONS/MONITORING: Provide all limitations and monitoring requirements being placed on each outfall.
	SEE TABLE II - ATTACHMENT 5
19.	EFFLUENT LIMITATIONS/MONITORING RATIONALE: Attach any analyses of an outfall by individual toxic parameter. As a minimum, it will include: statistics summary (number of data values, quantification level, expected value, variance, covariance, 97th percentile, and statistical method); wasteload allocation (acute, chronic and human health); effluent limitations determination; input data listing. Include all calculations used for each outfall and set of effluent limits and those used in any model(s). Include all calculations/documentation of any antidegradation or antibacksliding issues in the development of any limitations; complete the review statements below. Provide a rationale for limiting internal waste streams and indicator pollutants. Attach chlorine mass balance calculations, if performed.

Attach any additional information used to develop the limitations, including any applicable water quality standards calculations (acute, chronic and human health).

Industrial Facility - NA

11.

RELIABILITY CLASS:

OTHER CONSIDERATIONS IN LIMITATIONS DEVELOPMENT:

VARIANCES/ALTERNATE LIMITATIONS: Provide justification or refutation rationale for requested variances or alternatives to required permit conditions/limitations. This includes, but is not limited to: waivers from testing requirements; variances from technology guidelines or water quality standards; WER/translator study consideration; variances from standard permit limits/conditions.

DESCRIBE IN ATTACHMENT

SUITABLE DATA: In what, if any, effluent data were considered in the establishment of effluent limitations and provide all appropriate information/calculations.

All suitable effluent data were reviewed.

ANTIDEGRADATION REVIEW: Provide all appropriate information/calculations for the antidegradation review.

The receiving stream has been classified as tier 1; therefore, no further review is needed. Permit limits have been established by determining wasteload allocations which will result in attaining and/or maintaining all water quality criteria which apply to the receiving stream, including narrative criteria. These wasteload allocations will provide for the protection and maintenance of all existing uses.

ANTIBACKSLIDING REVIEW: Indicate if antibacksliding applies to this permit and, if so, provide all appropriate information.

There are no backsliding issues to address in this permit (i.e., limits as stringent or more stringent when compared to the previous permit). ${\tt SEE}$ ATTACHMENT 6

20. SPECIAL CONDITIONS RATIONALE: Provide a rationale for each of the permit's special conditions.

SEE ATTACHMENT 7

21. TOXICS MONITORING/TOXICS REDUCTION AND WET LIMIT SPECIAL CONDITIONS RATIONALE:

Provide the justification for any toxics monitoring program and/or toxics reduction program and WET limit.

SEE ATTACHMENT 8

22. <u>SLUDGE DISPOSAL PLAN</u>: Provide a description of the sludge disposal plan (e.g., type sludge, treatment provided and disposal method). Indicate if any of the plan elements are included within the permit.

N/A

23. MATERIAL STORED: List the type and quantity of wastes, fluids, or pollutants being stored at this facility. Briefly describe the storage facilities and list, if any, measures taken to prevent the stored material from reaching State waters.

SEE ATTACHMENT 9

24. RECEIVING WATERS INFORMATION: Refer to the State Water Control Board's Water Quality Standards [e.g., River Basin Section Tables (9 VAC 25-260-5 et seq.). Use 9 VAC 25-260-140 C (introduction and numbered paragraph) to address tidal waters where fresh water standards would be applied or transitional waters where the most stringent of fresh or salt water standards would be applied. Attach any memoranda or other information which helped to develop permit conditions (i.e. tier determinations, PReP complaints, special water quality studies, STORET data and other biological and/or chemical data, etc.

SEE ATTACHMENT 10

25. <u>305(b)/303(d) Listed Segments</u>: Indicate if the facility discharges to a segment that is listed on the current 303(d) list and, if so, provide all appropriate information/calculations.

This facility discharges directly to Deep Creek to the Southern Branch of the Elizabeth River and directly to the Southern Branch of the Elizabeth River. This receiving stream segment has been listed in Category 5 of the 305(b)/303(d) list for non-attainment of 1) dissolved oxygen standard for open water - summer months, 2) fish consumption due to PCB in fish tissue and Dioxin, 3) aquatic life use - benthic organisms. A TMDL has not been prepared or approved for this stream segment. The permit contains a TMDL reopener clause which will allow the it to be modified, in compliance with Section 303(d)(4) of the Act once a TMDL is approved.

EPA approved the Enterococci TMDL on July 20, 2010 for the Elizabeth Watershed Report. The facility was not assigned an individual waste load allocation for Enterococci. EPA also approved Nitrogen, phosphorus and TSS TMDL for the Chesapeake Bay TMDL on December 29, 2010. This facility was listed under the Bay Segment SMEMH as a non-significant discharger. Because an aggregate WLA exists, this permit did not receive an individual WLA. The permit contains water quality based limits for TSS and TP. The permit contains monitoring for TN and Enterococci. The permit also contains a TMDL reopener to allow the permit to be modified in the future to address individual waste load allocations.

SEE ATTACHMENT 11

26. CHANGES TO PERMIT: Use TABLE III(a) to record any changes from the previous permit and the rationale for those changes. Use TABLE III(b) to record any changes made to the permit during the permit processing period and the rationale for those changes [i.e., use for comments from the applicant, VDH, EPA, other agencies and/or the public where comments resulted in changes to the permit limitations or any other changes associated with the special conditions or reporting requirements].

SEE ATTACHMENT 12

27. NPDES INDUSTRIAL PERMIT RATING WORKSHEET:

TOTAL SCORE: 600 SEE ATTACHMENT 13

28. <u>DEQ PLANNING COMMENTS RECEIVED ON DRAFT PERMIT</u>: Document any comments received from DEQ planning.

The discharge is in conformance with the existing planning documents for the area.

OR

The discharge is not addressed in any planning document but will be included when the plan is updated.

29. <u>PUBLIC PARTICIPATION</u>: Document comments/responses received during the public participation process. If comments/responses provided, especially if they result in changes to the permit, place in the attachment.

<u>VDH/DSS COMMENTS RECEIVED ON DRAFT PERMIT</u>: Document any comments received from the Virginia Dept. of Health and the Div. of Shellfish Sanitaiton and noted how resolved.

The VDH reviewed the application and waived their right to comment and/or object on the adequacy of the draft permit.

The DSS provided comments by letter dated September 19, 2011.

The project is located in condemned shellfish growing waters and the activity, as described, will not cause an increase in the size or type of the existing closure.

EPA COMMENTS RECEIVED ON DRAFT PERMIT: Document any comments received from the U.S. Environmental Protection Agency and noted how resolved.

EPA waived the right to comment and/or object to the adequacy of the draft permit.

\mathbf{OR}

EPA has no objections to the adequacy of the draft permit.

OR

By letter dated _____, the EPA provided the following comments:

ADJACENT STATE COMMENTS RECEIVED ON DRAFT PERMIT: Document any comments received from an adjacent state and noted how resolved.

Not Applicable.

OTHER AGENCY COMMENTS RECEIVED ON DRAFT PERMIT: Document any comments received from any other agencies (e.g., VIMS, VMRC, DGIF, etc.) and noted how resolved.

Not Applicable.

OTHER COMMENTS RECEIVED FROM RIPARIAN OWNERS/CITIZENS ON DRAFT PERMIT: Document any comments received from other sources and note how resolved.

The application and draft permit have received public notice in accordance with the VPDES Permit Regulation, and no comments were received.

OR

The application and draft permit have received public notice in accordance with the VPDES Permit Regulation. Section 9 VAC 35-31-310 of the VPDES Permit Regulation states, in part, "The Board shall hold a public hearing whenever it finds, on the basis of requests, a significant degree of public interest in a draft permit(s)."

DESCRIBE PN COMMENTS AND RESOLUTIONS. PROVIDE PUBLIC HEARING DATE AND REFERENCE BACKGROUND MEMORANDUM, IF APPROPRIATE.

PUBLIC NOTICE INFORMATION: Comment Period: Start Date End Date

Persons may comment in writing or by e-mail to the DEQ on the proposed reissuance of the permit within 30 days from the date of the first notice. Address all comments to the contact person listed below. Written or e-mail comments shall include the name, address, and telephone number of the writer, and shall contain a complete, concise statement of the factual basis for comments. Only those comments received within this period will be considered. The Director of the DEQ may decide to hold a public hearing if public response is significant. Requests for public hearings shall state the reason why a hearing is requested, the nature of the issues proposed to be raised in the public hearing and a brief explanation of how the requestor's interests would be directly and adversely affected by the proposed permit action.

All pertinent information is on file and may be inspected, and arrangements made for copying by contacting Melinda Woodruff at: Department of Environmental Quality (DEQ), Tidewater Regional Office, 5636 Southern Boulevard, Virginia Beach, VA 23462. Telephone: 757-518-2174 E-mail: Melinda.Woodruff@deq.virginia.gov

Following the comment period, the Board will make a determination regarding the proposed reissuance. This determination will become effective, unless the Director grants a public hearing. Due notice of any public hearing will be given.

30. ADDITIONAL FACT SHEET COMMENTS/PERTINENT INFORMATION:

ATTACHMENT 1

SITE INSPECTION REPORT/MEMORANDUM



COMMONWEALTH of VIRGINIA

DEPARTMENT OF ENVIRONMENTAL QUALITY TIDEWATER REGIONAL OFFICE

Doug Domenech Secretary of Natural Resources 5636 Southern Boulevard, Virginia Beach, Virginia 23462 (757) 518-2000 Fax (757) 518-2009 www.deq.virginia.gov

David K. Paylor Director

Maria R. Nold Regional Director

November 1, 2011

Paul E. Dickson - Environmental Supervisor Dominion - Chesapeake Energy Center 2701 Vepco Rd. Chesapeake, VA 23323

Re: Technical Inspection Report.

Dominion – Chesapeake Energy Center (VA0004081)

Dear Mr. Dickson:

Enclosed is a copy of the technical inspection report prepared for the inspection conducted on September 15, 2011. Please note the deficiencies cited in this report and implement appropriate corrective measures in order to ensure continued permit compliance. Within thirty (30) days of receipt of this letter, you are requested to submit a letter documenting that the necessary corrections have been made.

This letter is not intended as a case decision under the Virginia Administrative Process Act, Va. Code § 2.2-4000 et seq.

If you have any questions regarding this report, please feel free to contact me at the above address or telephone (757) 518-2027.

Sincerely,

Steven J.E. Long

Environmental Specialist II

Enclosure

DEQ/OWCP: S.G. Stell

DEQ/TRO: File

Facility:	Dominion – Chesapeake Energy Center
County/city:	Chesapeake

VPDES NO.	VA0004081

DEPARTMENT OF ENVIRONMENTAL QUALITY WASTEWATER FACILITY INSPECTION REPORT PART 1

Inspection date:	Sept	tember 15,	2011	Date	Date form completed: October 18, 2011						
Inspection by:	Ste	ven J.E. L	ong	Insp	pection agency: DEQ/TRO)	
Time spent:		10 hours		Ann	Announced Inspection: [] Yes [√] No						
Reviewed by: Kenneth T. Rau			***				taken at site	e? [√]	Yes []	No	
Present at inspection:	Paul E Melind	. Dickson - a Woodrui	- Environ ff – DEQ i	men Perm	ntal Supervisor nit writer						
FACILITY TYPE:					FACILI	TY CLA	\SS:				
() Municipal					(√) M	lajor					
(√) Industrial					() Mi	inor					
() Federal					() Sr	nall					
() VPA/NDC			() Hi	gh Prior	rity ()	Low Priorit	ty				
TYPE OF INSPECTION:	week years years or and the second	inspection									
Routine √	0/00//		· · · · · · · · · · · ·		mpliance/ass	istance/con					
Date of previous inspection:			3/29/10			gency:			DEQ/TRO		
Population Served:	Connections			is Ser	ved		···				
Last Month Average Effluent: Outfall 001	TP (mg/l)	0.16	TRC (mg/l)		<ql< td=""><td>Flow MGD)</td><td>618</td><td>pH (s.u.)</td><td>7.4 - 7.5</td></ql<>		Flow MGD)	618	pH (s.u.)	7.4 - 7.5	
	Other:										
Last Month Average Effluent: Outfall 002	TP (mg/l)	0.20	TSS (mg/l)		19	Flow (MGD)		0.598	pH (s.u.)	8.1 - 8.4	
	Other:	TN = <0.3	0 mg/L, (O&G	= 5.0 n	ng/L, I	NH ₃ = <ql< td=""><td></td><td></td><td></td></ql<>				
Last Month Average Effluent: Outfall 003	TPH (mg/l)	*	TSS (mg/l)		12		Flow MGD)	0.247	рН (s.u.)	7.3	
1 st Semi-Annual 2011	Other:	Cu = <ql< td=""><td>, Zn = 46</td><td>ug/L</td><td>(disso</td><td>olved n</td><td>netals)</td><td></td><td></td><td></td></ql<>	, Zn = 46	ug/L	(disso	olved n	netals)				
Data verified in preface:		Upda	ted?				NO CH	ANGES?	 	٧	
Has there been any new constr	•			YES		NO	٧				
If yes, were the plans and spec		YES				NO	na				
DEQ approval date:	na		100								
COPIES TO: (x) DEQ/TRO; (COPIES TO: (x) DEQ/TRO; (x) DEQ/OWCP; (x) OWNER; () OPERATOR; () EPA-Region III; () Other:										

See Inspection Comments in the Summary section of this report for all items marked with an asterisk or an X.

	PLANT OPERATION AND MAINTENANCE													
1.	Class/number of licensed operators:		1	1	II.			181	1	IV		Tra	inee	
2.	Hours per day plant manned?						24 ho	urs p	er da	y, 7 d	lays pe	r weel	(
3.	Describe adequacy of staffing	7	А	VERA	\GE		PO							
4.	Does the plant have an established prog	jram fo	or trai	ning p	ersonne	əl					YES	7	NO	
5.	Describe the adequacy of training GOOD √ AVERAG											PO	OR	
6.	Are preventative maintenance tasks scheduled											1	NO	
7.	Describe the adequacy of maintenance GOOD √ AVERAGE											PC	OR	
	Does the plant experience any organic/hydraulic overloading?												NO	1
8.	If yes, identify cause/impact on plant na													
9.	Any bypassing since last inspection?										YES		NO	1
10.	Is the standby electrical generator opera	itional?	,					YE	s		NO		NA	1
,	How often is the standby generator exer	cised?	1							n	na			
11.	Power transfer switch?			na		AL/	ARM S	YSTE	EM?		na			
12.	When was the cross connection last test	ted on	the p	otable	supply	?						n	a	
13.	Is the STP alarm system operational?							YE	:S		NO		NA	1
14.	Is sludge disposed in accordance with a	n appr	oved	SMP				YE	s		NO		NA	1
	Is septage received by the facility?										YES		NO	4
	Is septage loading controlled?							YE	s		NO		NA	1
15.	Are records maintained?							YE	s		NO		NA	1

	OVERALL APPEARANCE OF FACILITY	GOOD	4	AVERAGE	POOR
--	--------------------------------	------	---	---------	------

				PLANT	RECORDS						The I was a second to the	20, 27, 30, 30, 30, 30, 30, 30, 30, 30, 30, 30	
·	WHICH	OF TH	E FOLLO	WING F	RECORDS DOES	S THE	PLANT	MAIN7	AIN?				
	Operational logs for each pro	cess u	nit	·	·		YES	1	NO		NA		
	Instrument maintenance and	calibra	tion				YES	٧.	NO		NA		
	Mechanical equipment maint	enance					YES	7	NO		NA		
1.	Industrial waste contribution	(munici	pal faciliti	es)			YES		NO		NA	√	
		W	IAT DOE	S THE C	PERATIONAL L	.og c	ONTAL	N					
	Visual Observations	1	F	low Mea	asurement	1		Labora	atory Res	sults		1	
2.	Process Adjustments		С	ontrol C	alculations				Other?				
COMMENTS: Laboratory records and activity logs are maintained.													
	WHAT DO	THE M	ECHANIC	CAL EQ	UIPMENT RECO	RDS	CONTA	IN?			NA	1	
	MFG. Instructions	√	A	s Built P	lans/specs	Spare Parts Inventory					√		
3.	Lube Schedules	√		Otl	ner?	Equipment/parts Suppliers				rs	V		
COMMENTS:													
	WHAT DO INDUSTR	RIAL WA	STE CO	NTRIBU	TION RECORDS	S CON	ITAIN?	(MUNIC	IPAL)		NA .	1	
	Wast	e Char	acteristics	;				Impa	act on Pla	ant			
4.	Location	and Dis	charge T	ypes			Other?						
COMN	MENTS:			, ,	-								
	WHICH OF THE FOLLOW	VING R	ECORDS	ARE A	T THE PLANT &	AVAII	LABLE	TO PER	RSONNE	L?	NA		
	Equipment Maintenand	e Reco	rds	4	. In	dustri	al Conti	ibutor R	Records				
5.	Operational Log	√ .	Samp	ling/testi	ng Records	4	lt.	nstrume	ntation R	Record	Ś	1	
6.	Records not normally availal	ole to pe	ersonnel a	at their lo	ocation:	Na	-						
7.	Were the records reviewed of	luring tl	ne inspec	tion		-			YES		NO	√*	
8.	Are records adequate and th	e O&M	manual c	current?		······································			YES	4	NO		
9.	Are the records maintained f	or the r	equired 3	-year tim	ne period		- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		YES	1	NO		
COM	MENTS: *Records obtained a	and rev	iewed af	ter the s	ite visit.								

		SA	MPLING	1900 (D) 1900 (D)								
1.	Are sampling locations capable of pro-	viding represer	ntative san	nples	s?			YES	1	N	0	
2.	Do sample types correspond to VPDE	S permit requir	rements?					YES	√*	N	0	
3.	Do sampling frequencies correspond t	o VPDES perm	nit requirer	nent	s?			YES	√	N	0	
4.	Does plant maintain required records	of sampling?						YES	4	N	0	
5.	Are composite samples collected in pr	oportion to flov	v?			YES		NO		N	Α	V
6.	Are composite samples refrigerated di	uring collection	?			YES		NO		N	A	√
7.	Does the plant run operational control	tests?				YES		NO		N	A	√
COMMENTS: See laboratory report for additional information concerning sampling.												
TESTING												
	Who performs the testing?	Plant	1	С	entral Lab	, -	1	Comm	nercial	Lab		1
Name: Plant performs field testing. Central and Commercial laboratory performs laboratory analyses.												
IF THE PLANT PERFORMS ANY TESTING, PLEASE COMPLETE QUESTIONS 2-4												
2.	Which total residual chlorine method is	s used?			Hach P	ocket	colorin	neter; \$	Std Mt	h 450)0-Cl	G
3.	Does plant appear to have sufficient e	quipment to pe	erform requ	uired	tests?				YES	*	NO	
4.	Does testing equipment appear to be	clean and/or or	perable?						YES	*	МO)
СОМ	MENTS: *Laboratory equipment not o	observed.										
The second secon	FOR INDUSTRIAL F.	ACILITIES WIT	TH TECHN	IOL(OGY BAS	ED LII	AITS O	NLY	And the second s	Active Control		
1.	Is the production process as described changes in comments section.	d in permit app	lication? I	f no,	describe		YES		NO		NA	1
2.	Are products/production rates as desc differences in comments section.	ribed in the pe	rmit applic	atior	n? If no lis	st	YES		NO		NA	1
3.	Has the Agency been notified of the c Date agency notified:	hanges and the	eir impact	on p	lant efflue	nt?	YES		NO		NA	1
сом	MENTS:		<u>.</u>									

	PROBLEMS IDENTIFIED AT LAST INSPECTION:	CORRECTED	NOT CORRECTED
AHERANGERIA	None noted.		

SUMMARY

INSPECTION COMMENTS:

Arrived on site at 0945 to perform unannounced inspection and reached Mr. Paul Dickson through the security office. Mr. Dickson was off site at the time though made arrangements to return to the facility at 1100. Agency personnel returned to the site at 1100 and met with Mr. Dickson. Discussed the site visit including a review and familiarization for Ms. Melinda Woodruff the facility's permit writer. A site survey was conducted reviewing a majority of the site though not all areas were observed. No housekeeping issues were noted from the survey with the site appearing to be well managed.

A review of the Stormwater Pollution Prevention Plan (SWP3) finds a well prepared document. The plan date is November 2009 and was signed, including the non-stormwater certification December 2009. The last non-stormwater discharge assessment and certification was signed June 2011.

The plan provides that inspections are performed on a weekly, monthly and quarterly basis. Inspection records were provided and well documented and detailed. Training is performed annually and is also well documented with training last performed October 2010.

The comprehensive site compliance evaluation is conducted annually and is also well prepared. The last inspection was conducted December 2010 and detailed the scope of the inspection, but did not identify any non-compliance issues for the summary report. Two action items were identified for Outfalls 016 and 010 and were completed within the month. The evaluation is signed but does not include the certification reference in Part I.F.4.d.4.(c) stating that the evaluation is to be signed according to Part II.K. This has been discussed with the facility contact and a certification required by Part II.K has been added.

Representative discharges are noted in the Permit with Outfall 016 representing Outfall 017. A review of the SWP3 finds nothing in the plan for the representative sampling. Part I.F.3.d of the Permit provides that representative sampling is acceptable though there is information required to be included in the SWP3. Representative monitoring is also allowed for the quarterly visual monitoring required under Part I.F.3.e though from the records review it appears that sampling for this monitoring is performed at Outfall 017. Facility personnel will be reviewing this requirement and making additions as needed for resolution.

Page 41 of the SWP3 details the "regularly occurring discharges of allowable non-stormwater discharges" as required by Part I.F.3.g.2. This includes "fire fighting activities" which should not be a "regularly occurring discharge". This item is to be eliminated from the SWP3. Page 41 also lists routine wash down – "As necessary to control slip hazards created in wet areas". From this description it was not clear which of the non-stormwater discharges this was considered. Facility contact provides this is pavement wash down water, "item g' as referenced in the Permit. Additional information is to be added to the SWP3 clarifying the use of this wash water to support it as an authorized non-stormwater discharge.

Outfall 016 and 017 are included in a Stormwater Management Evaluation for dissolved zinc and Outfalls 011, 012, 016 and 030 for toxicity. A report is due each February with the last report received February 9, 2011.

VA0004081

INSPECTION COMMENTS (continued):

Quarterly visual monitoring is performed and also well documented. There are several instances where the discharge is reported with poor qualities. Typical visual qualities included colored (gray/black and slight brown), and reported some discharges had turbidity. Many of these are attributed to plant decomposition though there were some reported issues with coal fines and fly ash. Nothing in the report provides for the evaluation of the current best management practices or if additional practices are needed to reduce or eliminate the pollutants from leaving the site.

Odor was reported in several examinations; some reported to have a strong sulfur smell while others only reported a "slight odor" with no further explanation. The sulfur smell could be from naturally occurring sulfur compounds. When an odor is reported additional information concerning the type of odor encountered should be provided along with its potential source.

Mr. Dickson provided that there is additional information included in the activity logs that will provide for corrective actions. It was suggested that a direct connection from the observations made and any of their eventual corrective actions applied be either referenced or included with the quarterly visual examination.

Areas observed during the site survey included:

- Outfall 001 discharge channel
- . Metals cleaning waste pond
- Coal Pile and coal pile runoff treatment pond
- AST associated with Outfall 301
- Outfall 003, 011 and 012
- The screen wells for the cooling water intake
- · Chlorination building
- Drainage areas around Outfalls 010, 016 and 017
- The perimeter road for the ash landfill
- The oil waste pond, bottom ash pond and Outfall 002 area.
- · Outfall 018 areas

There were no problems observed throughout these areas with the roadway and major industrial areas that were observed being well managed. Considering the industrial activity, the site did appear to be very clean.

Observations at Outfall 001 found a discolored area at the headwaters. Mr. Dickson provided that this change in color is likely from air bubbles that are coming to the surface of the tannin rich waters. Attached photographs do show this discolored area from the center of the channel following the land and concentrated near rocks at the shoreline. It was later found that a discharge was occurring from the demineralizer at the time of our observations. It is possible that the demineralizer discharge, containing very fine bubbles, created the discoloration. The start of the discolored water is in the vicinity of the discharge pipe for the demineralizer with the bubbles coming to the surface downstream. To verify this it is suggested that the discharge point be observed during demineralizer discharges to confirm that that the discoloration is from the bubbles. This could be compared to the actual demineralizer discharge that is typically clear and colorless.

The area around the truck wash facility near Outfall 016 was observed with some concerns for water discharging from this facility. Water in puddles was observed and there is some indication that water is running over the road and into the curb. The source of this water was not known nor was an actual discharge of water observed. This is not believed to be from rainfall with the last rain event occurring over six days ago. (Rainfall is documented on the 15th but occurred later in the night.) This must to be reviewed during truck washing to determine if there is a potential for the process wastewater to discharge. If there is a potential for the loss of the process wastewater, steps are needed to ensure that this water is not discharged or the facility must apply for a modification of the permit to account for this discharge.

INSPECTION COMMENTS (continued): The final area observed was for Outfall 018. Upon reviewing the permit, maps and the recent permit application it was noted that Outfall 018 show four different discharge points. The drainage area included for these discharges include the metals cleaning waste pond, the switch yard, parking lots, and open fields. These areas are considered industrially regulated with monitoring not required. The site map shows these areas discharging to "wetlands". The wetlands are then shown to flow to the east and out four culvert pipes to the discharge canal. The actual discharges should be from the drainage discharges that go into the wetlands and should be shown as separate discharge points. The wetland discharge to the drainage ditch does not need to be noted as a discharge point. This will be addressed with the Permit writer and should be resolved with the issuance of the new Permit. COMPLIANCE RECOMMENDATIONS FOR ACTION Include all information as specified in the Permit under Part I.F.3.d for the representative sampling of Outfall 016 for Outfall 017. Review the truck wash facility in the drainage area for Outfall 016 during washing operations and determine if there is a discharge of wastewater from this area. Eliminate any potential for discharge or apply for a permit modification.

			UNIT PI	ROCESS:		Industrial Pond Metals Cleaning Waste Pond Oily Waste Pond									
													YES	NO	NA
1.	Type of filte	ers	A	erated		Polis	hing			Una	aerated	4			
2.	Number of	cells		one cell f	or both	ponds									
3.	Number ce	lls in operation	on		one ea	ch		. "							
	Operation	of system	···												
4.	Se	ries	√	Pa	arallel					Other:					
	Color									Light E	Brown				
5.	Gray	Oily B	rown	Gr	een	Metals			Oth	er:					
			ΕV	IDENCE O	FTHEF	OLLOV	VING	PROBL	LEMS	t .				Company of the compan	
	Vegetation	in lagoon or	dikes?											√	
	Rodents bu	irrowing on d	likes?											√.	
	Erosion?													√	
	Sludge bars?												√	.	
	Excessive foam?													√	
6.	Floating ma	aterial?												√	
7.		are lagoon co				,									1
8.		is aeration sy		erating pro	perly?		ι					1			1
9.	Odors:		eptic	<u> </u>	arthy		N	one	1		Other:		i		
10.	Fencing int												1		
11.		ntained prope											1		
12.		ol valves wo		perly?			<u> </u>			Т.Т		<u> </u>			1
13.		charge eleva	ation?			Тор		Mic	ddle	- √	Bottom	1 1			
14.	Freeboard				1							1	1		
15.		e of effluent?			GO	ÓD	1	FA	AIR		POOR			ı	
		ring wells pre				Placen	nent d	of moni	itorin	g wells	was not che	cked.	ļ		
	Are wells a	dequately pr	otected	from runoff?	?										
16.	Are caps o	n and secure	ed? 												
GENE	RAL COND	тюп:		GOOD		_ √			FAII	R			POOR		
COMM	MENTS:	Both of the	se pond	is are lined	I. Solids	s (slud	ge ba	ır) was	obse	rved in	the oily was	te pond r	ear the		

UNIT PROCESS:	EFFLUENT/PLANT OUTFALL	

									YES	NO	NA
1.	Type of outfall			Shore Based √		Submerged	√				
		E IF SHORE BASED:									
2.	Wingwall		Headwall	7	Rip Rap	1	Pipe	4			
3.	Flapper valve present?									1	
4.	Erosion of bank area?									1	
5.	Effluent plume visible?									1	
	Condition of outfall and the supporting structure?										
6.	GOOD	GOOD √ FAIR POOR									
	FINAL EFFLUENT, EVIDENCE OF FOLLOWING PROBLEMS?										
	Oil sheen?									1	
	Grease?									1	
	Sludge bar?									1	
	Turbid effluent?									1	
	Visible foam?									*	
7.	Unusual color?										


					the state of the s	
				1		
AFIGER & CALIFORNIA	0000			ľ		
LGENERALCONIDITION: 1	(4()())	· v	FAIR	ì	POOR I	
	0000	,	17303	i i	1 001	
					· · · · · · · · · · · · · · · · · · ·	

COMMENTS:


Outfalls 001, 002, 003, 010, 016, 017, and 018 were observed without a specific issue. Foam was observed in the headwaters of Outfall 001 but was not discharged at the end of the canal. Outfall 016 needs to be checked for discharges when truck washing is occurring.




1) Headwaters of Outfall 001. Discolored water can be seen from the middle of the canal to the rocks. This could be from the discharge from Outfall 101 and bubbles resulting from the demineralizer discharge.




2) Outfall 001 canal and boom to capture debris.




3) Coal pile runoff pond with pond entrance in the foreground. Curbing is in place to capture some of the solids.




4) Discharge point for the coal pile treatment pond. This discharges to Outfall 003.




5) Outfall 016 drainage area with the carbon burning facility and the truck wash in the blue building.



6) Outfall 016 access point.




7) Truck washing site with pooled water outside of the containment area.



8) Wet area from the truck wash does provide some indication of loss of the process water to the roadway. This is in the area of Outfall 016 which is a 'stormwater-only' discharge. This should be reviewed during operations to determine if a discharge is occurring.




9) Metals cleaning pond near the entrance of the facility.



10) Discharge pipe for the metals cleaning pond at bottom ash pond.



11) Oily waste pond for Outfall 002. Majority of this flow is from the center of the site near the generation building. A "sludge bar" of solids was observed at the entrance pipe to this pond.



 Discharge from the oily waste pond. Observed to be clear and colorless.



COMMONWEALTH of VIRGINIA

DEPARTMENT. OF ENVIRONMENTAL QUALITY TIDEWATER REGIONAL OFFICE

Doug Domenech Secretary of Natural Resources 5636 Southern Boulevard, Virginia Beach, Virginia 23462 (757) 518-2000 Fax (757) 518-2009 www.deq.virginia.gov

David K. Paylor Director

Francis L. Daniel Regional Director

November 1, 2011

Paul E. Dickson – Environmental Supervisor Dominion – Chesapeake Energy Center 2701 Vepco Rd. Chesapeake, VA 23323

Re: Laboratory Inspection

Chesapeake Energy Center (VA0004081)

Dear Mr. Dickson:

Enclosed is a copy of the inspection report for the laboratory records review associated with the site visit on September 15, 2011. Please note that the Laboratory Evaluation Section of the report identifies that the Laboratory Records Section requires correction. The report identifies the specific deficiencies and makes recommendations for corrective measures. The General Sampling and Analysis section further identifies an issue with sampling procedures for one of the internal Outfalls. Though this item is not considered a deficiency, it is addressed in this report.

In view of the significance attached to proper sampling and analysis of samples for use in complying with the terms of your VPDES/VPA permit, please review the attached report and make the appropriate corrections to ensure permit compliance. To avoid possible enforcement action, within twenty (20) days of receipt of this letter send a written notification to this office of the corrective measures that you have implemented. If you have not taken corrective action and/or responded to this office in writing by the above deadline, this matter will be referred to the Regional Compliance Auditor and a Warning Letter (WL) may be issued.

This letter is not intended as a case decision under the Virginia Administrative Process Act, Va. Code § 2.2-4000 *et seq*. If you have any questions regarding this report, please contact me or Mr. Kenneth T. Raum at the above address or telephone (757) 518-2000.

Sincerely,

Steven J.E. Long

Environmental Specialist II

Enclosure

: DEQ/OWCP: S.G. Stell

DEQ/TRO: File

DEPARTMENT OF ENVIRONMENTAL QUALITY - WATER DIVISION LABORATORY INSPECTION REPORT

10/01

	TY NO:	INSPECTION DATE: 9/15/11	PREVIOUS INSP. DATE: PREVIOUS 3/25/10 PREVIOUS				N: '	TIME SPENT: 10 hours		
VA004081 9/15/11 NAME/ADDRESS OF FACILITY:				No deficiencies		UNANNOUNCED				
Dominion – Chesapeake Energy Center			(√) MAJOR	()	CILITY TYPE: MUNICIPAL	INSF (√) YE		SPECTION? YES		
2701 Vepco Rd. Chesapeake, VA 23323		() MINOR	(√)	INDUSTRIAL		() NO				
			() SMALL	SMALL () FEDERAL			FY-SCHEDULED INSPECTION?			
			() HIGH PRIORITY	HIGH PRIORITY () VPA/NDC			(√) YES () NO			
			() LOW PRIORITY	()	COMMERCIAL	1 ` '				
INSPE	CTOR(S):		REVIEWERS:				NSPECTION:			
Steven	J.E. Lon	g	Kenneth T. Raum / 10-		1 Paul Dicksor	– Envi	ronmen	tal Supervisor		
	dina t	LABORATO	RY EVALUATION			Company of the Compan	DEFICI	ENCIES?		
						Υ	es	No		
LABOR	RATORY	RECORDS					X			
GENE	RAL SAM	PLING & ANALYSIS						*		
		ased on a records review med September 15, 2011.		asso	ociated with the		···			
	•			· · · · · ·						
					~			·		
C	QUALITY	ASSURANCE/QUALITY (CONTROL							
Y/N	QUALIT	Y ASSURANCE METHO	PARAMETERS			FRE	QUENC	Υ		
	REPLIC	ATE SAMPLES								
		SAMPLES								
		ARD SAMPLES								
		AMPLES								
		E BLANKS	1							
	OTHER		DATE: CAR		<i>**</i>	<u></u>	00.110			
		IR QA DATA?			eficiency () Defic		(X) NA			
		/IPLES PROVIDED?			ficiency () Defic		(X) NA			
COPIE	COPIES TO: (x) DEQ - RO; (x) OWCP; () VDH-DWE; (x) OWNER; () EPA-Region III; () Other:									

[Protect in a visco to i										
LABORATORY RECORDS SECTION										
LABORATORY RECORDS INCLUDE THE FOLLOWING:										
√	SAMPLING DATE	СОИТ МО	ONITORING CHART							
√	SAMPLING TIME	MENT CALIBRATION								
√	SAMPLE LOCATION	INSTRUM	MENT MAINTENANCE							
		CERTIFIC	ICATE OF ANALYSIS							
WRITT	EN INSTRUCTIONS INCLUDE TH	HE FOL	LOWING:	•						
	SAMPLING SCHEDULES	ANALYSIS	S PROCEDURES							
			i na produce (na 2) se propies e un ancio (ne u e en esca Al lange e esta de la lange e en escala e en e			YES	NO	N/A		
DO AL	L ANALYSTS INITIAL THEIR WOI	₹ K ?						V		
DO BE RESU	NCH SHEETS INCLUDE ALL INF LTS?	ORMAT	TION NECESSARY TO DETE	RMINE				√		
IS THE	DMR COMPLETE AND CORREC	below.		Х						
ARE A	LL MONITORING VALUES REQU		Х							
GENERAL SAMPLING AND ANALYSIS SECTION										
		YES	NO	N/A						
ARE S	AMPLE LOCATION(S) ACCORDI		1							
ARE S	AMPLE COLLECTION PROCEDU		√*							
IS SAM	MPLE EQUIPMENT CONDITION A				4					
IS FLC	OW MEASUREMENT ACCORDING		√							
ARE C	ARE COMPOSITE SAMPLES REPRESENTATIVE OF FLOW? √									
ARE S	AMPLE HOLDING TIMES AND PI		√*							
IF ANALYSIS IS PERFORMED AT ANOTHER LOCATION, ARE SHIPPING PROCEDURES ADEQUATE? LIST PARAMETERS AND NAME & ADDRESS OF LAB: Dominion Central Laboratory; Universal Laboratories										
LABO	RATORY EQUIPMENT SECTION									
	and the state of t					YES	NO	N/A		
IS LAE	BORATORY EQUIPMENT IN PRO			7						
ARE ANNUAL THERMOMETER CALIBRATION(S) ADEQUATE?										
IS THE	IS THE LABORATORY GRADE WATER SUPPLY ADEQUATE? √									
ARE A	ARE ANALYTICAL BALANCE(S) ADEQUATE?									

FOR ASTERISK ITEMS (*) SEE LABORATORY INSPECTION REPORT SUMMARY PAGES FOR DETAILS.

DEPARTMENT OF ENVIRONMENTAL QUALITY - WATER DIVISION LABORATORY INSPECTION REPORT SUMMARY

10/01

FACILITY NAME: Dominion - Chesapeake Energy Center		VPDES NO:		VA0004081	9/15/11		
LABORATORY RATING			NO DEFICIENCIES				
		х	DEFIC	ENCIES			

LABORATORY RECORDS

Records reviewed: pH, calibration, Chlorine calibration, Technicians demonstration of initial competency, and the following monitoring periods and Discharge Monitoring Report:

November 2010 - Outfall 201

January 2011 - Outfalls 001, 002, and 206

1st Quarter 2011 – Outfalls 101, 301, 016 and 017.

1st Semi-annual 2011 - Outfalls 003, 010, 030, and 031

The Laboratory Records section has the following deficiencies:

- The Quantification Limit (QL) for TSS is defined in the Permit at 1.0 mg/L (Page 20, Part I.D.5.a). Part I.D.6.a provides that If all data are below the QL, then the average shall be reported as <QL. Part I.D.6.c states that "Any single datum required shall be reported as <QL if it is less than the QL listed in Part I.D.5.a.". Outfall 101 for the 1st quarter 2011 shows a result of <1.0 mg/L versus <QL.
- Dissolved zinc for Outfall 003 for the 1st semi-annual monitoring is reported as 46 ug/L. This parameter has a defined quantification limit of 50 ug/L. The correct reporting should be <QL.
- The TPH for Outfall 003 for the 1st semi-annual monitoring is NOT reported. Results were observed in the
 analytical data. This appears to be an omission. This has been reviewed with correction pending resolution of the
 TPH reporting noted below.
- TPH reporting when two fractions (DRO and GRO) are reported as "less than" should be reported as < the total of
 the two quantification limits. For the records reviewed both fractions were reported as <0.5 mg/L; the correct value
 should be reported as <1.0 mg/L. This issue was observed for several reports. Information for reporting the TPH
 was provided and is under review by facility personnel and considered resolved pending that review.
- Dissolved metals filtration not indicated on the reported on the Chemical Analysis Order for Outfall 003 sampled on 1/18/11. Dissolved metals filtration is reported for Outfall 011 but a time is not given. This issue has been resolved noting that the sampling procedure includes inline filtration of the sample upon its collection. This is to be included on the order sheet or the chain of custody to eliminate questions of this nature.

Corrective Actions: The following items have been discussed and resolved:

Properly report all parameters adhering to correct reporting criteria for those parameters with defined quantification limits. For those parameters that do not have defined quantification limits, report "less than" and the actual numerical value of the quantification limit as reported by the laboratory. Report the TPH parameter using the convention as provided via email. Include information as discussed for the field filtration of the dissolved metals.

The only item needing further resolution is submission of the corrected Discharge Monitoring Report for Outfall 003 that includes the TPH results.

VA0004081-091511L

3

GENERAL SAMPLING AND ANALYSIS

The General Sampling and Analysis section has the following item for sampling (Not considered a deficiency):

Outfall 201 is a grab sample of the metals cleaning basin. The Permit provides that sample shall be collected at the tap in the recirculation line at the pond. The Permit further states that "No wastewater shall be added to the basin after sample is collected prior to discharge for the sample period".

Current operating procedures provide for the sampling and the analysis of the pond at the tap with the discharge pending the results of this re-circulated pond water. Once the results are obtained and found to be within the Permit limits, a discharge is initiated and the results from the recirculation line are reported. An actual discharge sample is not taken.


The last discharge from this pond was in November 2010. Original sampling was performed on 10/29/10 with a comment noting that "These will be used for discharging in November". Results obtained for the October sampling showed the iron results at 1.4 mg/L, which is above the 1.0 mg/L Permit limit. Comments were observed indicating the need for further treatment for lowering the iron. Treatment does include addition of calcium hydroxide with recirculation of the pond water. Samples were then taken 11/16/10 with all parameters below the Permit limits and a discharge was stated at 0836 on 11/24/11.

Several concerns for the current sampling methodology and reporting are found. The samples obtained are representative of the pond conditions at the time of sampling. These results are not necessarily representative of the discharge occurring several days later. With some parameters dependent on temperature and pH, there could be significant differences from the time of the sampling to the time of the discharge. As currently written, though not operated in this manner, the facility could discharge months after the sampling event as long as no further wastewater is added to the basin.

Discussing this with both facility and agency personnel, nothing was provided that a comparison study was conducted to verify there was no difference. This issue was originally brought to the Permit writer's attention and will be addressed in the issuance of the new permit.

ATTACHMENT 2


DISCHARGE LOCATION/TOPOGRAPHIC MAP



ENSR AECOM ENSR CORPORATION 4701 COX ROAD, SUITE 200 GLEN ALLEN, VA 23060 PHONE: (804) 290-2493	QUADRANGLE: NORFOLK SOUTH	CHESAF	E LOCATIO PEAKE ENER ESAPEAKE, Y	RGY CENTER	FIGURE NUMBER
FAX: (804) 290-7921	1	DRAWN BY:	DATE	PROJECT NUMBER	DRAWING NUMBER:
WEB: HTTP://WWW.ENSR.AECOM.COM	NOT TO SCALE	LLM	6/15/07	02285-038	1 af 1

ATTACHMENT 3

SCHEMATIC/PLANS & SPECS/SITE MAP/ WATER BALANCE



ATTACHMENT 4

TABLE I - DISCHARGE/OUTFALL DESCRIPTION

TABLE I

NUMBER AND DESCRIPTION OF OUTFALLS

OUTFALL	DISCHARGE	DISCHARGE SOURCE		
NO.	LOCATION	(1)	TREATMENT (2)	(3 and 4)
			(See attached)	
001	36°45′45″ 76°18′15″	Discharge Canal which includes: Once through cooling water condenser, Units 1-4; Demineralized wastes (101); reverse osmosis concentrate; stormwater outfalls 013, 015, 018, 021; Hotwell dumps		519.5 MGD
101	Internal Outfall to 001	Demineralizer wastes and reverse osmosis waste to 001		0.128 MGD
002	36°45'45" 76°18'15"	Ash pond; metals treatment basin (201); sewage treatment plant (206); low volume wastes from Units 1-3 including floor drains, boiler blowdown, slope wash, Mobotec dike drainage; Carbon canister backwash, fan blade rinsing, localized boiler tube rinsing, boiler clinker removal, turbine flush water; low volume waste Unit 4 including floor drains, boiler blowdown, slope wash, equipment washing, caustic/acid tank dikes, fan blade rinsing, localized boiler tube rinsing, boil clinker removal, turbine wash water, SCR dike; bottom ash sluice; Unit 3 economizer hopper; structural fill run off/leachate; ash silo sump including truck wash and PMI facility; coal pile runoff; and reverse osmosis concentrate		1.37 MGD

OUTFALL NO.	DISCHARGE LOCATION	DISCHARGE SOURCE	TREATMENT (2) (See attached)	FLOW (3 and
201	Internal Outfall to 002	Metals treatment basin (cleaning wastes including air preheater wash water, precipitator wash water, duct wash water, chemical boiler cleaning, other chemical cleaning		Batch Discharge
206	Internal Outfall to 002	Sewage Treatment Plant		0.009 MGD
004	36°46′15″ 76°18′0″	Screen backwash units 1&2		0.72 MGD
005	36°46′15″ 76°18′0″	Screen backwash units 3&4		0.87 MGD
007	36°46′15″ 76°18′0″	River recirculation pit sump units 1&2		0.029 MGD
008	36°46′15″ 76°18′0″	River recirculation pit sump unit 3		0.029 MGD
009	36°46′15″ 76°18′0″	River recirculation pit sump units 4		0.029 MGD
019	36°46′15″ 76°18′0″	Fish return line units 1&2		Varies
020	36°46 ′ 15″ 76°18 ′ 0″	Fish return line units 3&4	·	Varies
031	36°46′15″ 76°18′0″	Chlorination building (uncontaminated river water)		Drain plugged, has not discharged
003	36°46′30″ 76°18′0″	Coal pile runoff, bermed bulk fuel oil storage area runoff (301), combustion turbine area runoff, synfuel wash water runoff overflow, coal dock storm water and wash water overflow		0.062 MGD

OUTFALL NO.	DISCHARGE LOCATION	DISCHARGE SOURCE	TREATMENT (2)	ELOW
			(See attached)	(3 and 4)
301	36°46′30″	Storm water from		0.002 MGD
	76°18′0″	bermed bulk fuel oil		valved and
		storage area		batch
		11111190 0100		discharge
010	36°46′15″	Storm water from ash		0.011 MGD
	76°18′0″	silos areas and truck		0.011 1100
		wash		
011	36°46′30″	Storm water from loop		0.010 MGD
	76°17′30″	(rail) track area that		valved and
		includes construction		batch discharge
		maintenance laydown area		-
		(steel fabrication,		
		portable diesel and gasoline storage,		
		equipment storage, lime		
		staging, south oil		
		storage tank and		
		material/		
		equipment/laydown)		
012	36°46′30″	Storm water runoff		0.008 MGD
	76°18 ′ 0″	from dismantled diesel		Valved and
		tank diked area and		batch
		loop track area		discharge
013	36°46′0″	Storm water runoff		0.001 MGD
	76°18 ′ 15″	from small area		
		adjacent to the		
		natural gas storage		
015	26046475#	facility and haul road		
015	36°46′15″ 76°18′15″	Storm water runoff		0.001 MGD
	10.18.12.	from drainage area		
		adjacent to and		
		including the training center		
016	36°46′15″	Storm water runoff		0.004.4400
010	76°18 ′ 0″	from road providing		0.004 MGD
	70 10 0	ingress and egress for		
		the ash silos,		
		warehouse docks,		
	:	sewage treatment		
		building, ash haul		
		road and scales, a		
		laydown area, carbon		
		burn out operations		
		(CBO)		
017	36°45′57″	Storm water runoff		0.005
	76°18 ′ 0″	from portion of the		3.000
		warehouse roof,		
		storage yard and ash		
		haul road with		
		possible groundwater		
_		associated		

OUTFALL NO.	DISCHARGE LOCATION	DISCHARGE SOURCE (1)	TREATMENT (2) (See attached)	FIOW (3 and 4)
018	36°46′0″ 76°18′15″	Storm water runoff from the station and visitor parking areas, a substation adjacent to the visitor parking area, pavilion area, undeveloped area west of discharge canal, and east southeast area of the metals pond		0.083 MGD
021	36°46′15″ 76°18′15″	Storm water runoff from drainage area adjacent to, and including the front of the administration building		0.002 MGD
030	36°45′45″ 76°18′15″	Storm water runoff from the coal unloading dock		0.001 MGD Currently all water goes to the coal pile treatment pond there has been no discharge

- List operations contributing to flow

- (2) Give brief description, unit by unit
 (3) Give maximum 30-day average flow for industry provided for in application
 (4) Storm water flow estimates calculated using 0.011 ft average rainfall values, 0.9 runoff coefficient for impervious surfaces and 0.6 runoff coefficient for pervious surfaces.

ATTACHMENT 5

TABLE II - EFFLUENT MONITORING/LIMITATIONS

- INDUSTRIAL EFFLUENT LIMITATIONS/MONITORING TABLE II

OUTFALL # 001

Outfall Description: Once through condenser cooling water; demineralizer regeneration waste and reverse (101); units 1-3 sump overflow; hotwell dumps osmosis waste water

SIC CODE: 4911

(x) Final Limits () Inte	() Interim Limits	Effective Dates -	From: Issuance	ance	To: Expiration	ration	
			EFFLU	EFELUENT LIMITATIONS	TIONS	MONITORING REQUIREMENTS	ING ENTS
PARAMETER & UNITS	BASIS FOR LIMITS	MULTIPLIBR OR PRODUCTION	MONTHLY	MINIMOM	MAXIMUM	FREQUENCY	SAMPLE TYPE
Flow (MGD)	က		N	MA	NL	1/Day	Est
рн (s.u.)	ю		NA	6.0	0.6	2/Month	Grab
Total Residual Chlorine (mg/1) [a] [b]	2		.021	NA	.026	2/Month	Grab
Total Phosphorus (mg/1)	င		2.0	NA	NA	2/Month	Grab
Total Nitrogen (mg/l)	m		N	NA.	NA	2/Month	Grab
Temperature (°C)	2		NA	NA	[c]	1/Year	[0]
Heat Rejection (BTU/HR)	m		3.55 x 10 (9)	NA	NA	Continuous	Record

NA = NOT APPLICABLE; NL = NO LIMIT, MONITORING REQUIREMENT ONLY

1/Year = Between January 1 and December 31

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

- See Parts I.D.5. and I.D.6. for quantification levels and reporting requirements, respectively. See Part I.D.15. for Total Residual Discharge Duration. See Part I.D.14 for Thermal Mixing Zone Requirements.
- ටු වූ මු
- There shall be no discharge of floating solids or visible foam in other than trace amounts. 2

- The basis for the limitations codes are:
 1. Technology (e.g., Federal Effluent Guidelines)
 2. Water Quality Standards (9 VAC 25-260 et. seq.)
 3. Best Professional Judgment

OUTFALL # 101 (internal outfall to 001)

Outfall Description: Demineralizer regeneration wastes and reverse osmosis wastes

SIC CODE: 4911

(x) Final Limits () Interim Limits	erim Limits	s Effective Dates -	From: Issuance		To: Expiration	on	
			OTHE HE HE HE HE HE HE HE HE HE HE HE HE H	EFELUENT LIMITATIONS	TIONS	MONITORING REQUIREMENTS	ING ENTS
PARAMETER & UNITS	BASIS FOR LIMITS	MULTIPLIER OR PRODUCTION	MONTHLY	MINIMUM	MAXIMUM	FREQUENCY	SAMPLE TYPE
Flow (MGD)	೮		NL	NA	NL	1/3 Months	Est.
Oil & Grease (mg/l)	⊣		15	NA	20	1/3 Months	Grab
Total Suspended Solids (mg/l)	П		30	NA	100	1/3 Months	Grab

NA = NOT APPLICABLE; NL = NO LIMIT, MONITORING REQUIREMENT ONLY

1/3 Months = In accordance with the following schedule: 1st quarter (January 1 - March 31); 2nd quarter (April 1 - June 30); 3rd quarter (July 1 - September 30); 4th quarter (October 1 - December 31).

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

2. There shall be no discharge of floating solids or visible foam in other than trace amounts

- 1. Technology (e.g., Federal Effluent Guidelines)
- 2. Water Quality Standards (9 VAC 25-260 et. seq.) 3. Best Professional Judgment

OUTFALL # 002

rnn Ash pond; metals treatment basin (201); sewage treatment plant (206); low volume wastes Units 1-3; low volume waste Unit 4; bottom ash sluice; Unit 3 economizer hopper; structural fill off/leachate; ash silo sump including truck wash, PMI facility; coal pile/dock runoff; reverse osmosis Outfall Description:

concentrate SIC CODE: 4911

SAMPLE TYPE Grab Grab Grab Grab Grab Grab Est REQUIREMENTS MONITORING 1/3 Months FREQUENCY 2/Month 2/Month 2/Month 2/Month 2/Month 2/Month To: Expiration MAXIMUM .026 0.6 Z NA 20 NA 50 EFFLUENT LIMITATIONS MINIMOM 0.9 ΝĀ NA NΑ NA ΝA ΝΆ From: Issuance AVERAGE MONTHLY .026 2.0 NL Z 15 NA 30 1 Effective Dates MULTIPLIER PRODUCTION () Interim Limits BASIS S H Z H Z H FOR ന $^{\circ}$ α ന $^{\circ}$ \vdash Total Residual Chlorine Total Phosphorus (mg/l) Total Suspended Solids Total Nitrogen (mg/1) & Grease (mg/l PARAMETER & UNITS (x) Final Limits [a Flow (MGD) pH (S.U.) (mg/1) (mq/1)Oil

= NO LIMIT, MONITORING REQUIREMENT ONLY NA = NOT APPLICABLE; NL

Grab

2/Month

H

NA

딛

 $^{\circ}$

m

Dissolved Copper (ug/1)

[a] [b]

Ammonia (mg/l)[a]

Grab

1/6 Months

ΝĪ

NA

Ϋ́

1/3 Months = In accordance with the following schedule: 1st quarter (January 1 - March 31); 2nd quarter (April 1 - June 30); 3rd quarter (July 1 - September 30); 4th quarter (October 1 - December 31). - June 30); 2nd half (July 1 1st half (January 1 1/6 Months = In accordance with the following schedule: December 31) Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

- See Parts I.D.5. and I.D.6. for quantification levels and reporting requirements, respectively. [a]
 - [b] See Part I.B. for Boiler Cleaning/Metals Requirements.
- There shall be no discharge of floating solids or visible foam in other than trace amounts. 2

- 1. Technology (e.g., Federal Effluent Guidelines)
- 2. Water Quality Standards (9 VAC 25-260 et. seq.) 3. Best Professional Judgment

OUTFALL # 201

Metals treatment basin Outfall Description:

SIC CODE: 4911

SAMPLE TYPE Grab Grab Grab REQUIREMENTS [a] Est Grab MONITORING FREQUENCY 1/Month 1/Month 1/Month 1/Month 1/Month To: Expiration MAXIMUM 100 NI 20 \leftarrow EFFLUENT LIMITATIONS MUMINIM NA NA NA NA NA From: Issuance AVERAGE MONTHLY NL 15 30 Н ı Effective Dates MULTIPLIER PRODUCTION () Interim Limits STIMII BASIS FOR ന \vdash --. Total Suspended Solids Total Copper (mg/1) PARAMETER & UNITS Total Iron (mg/l) Limits Oil & Grease Flow (MGD) Final (mg/1)(mq/1)(x)

NA = NOT APPLICABLE; NL = NO LIMIT, MONITORING REQUIREMENT ONLY

wastewater shall be added to the basin after sample is collected prior to discharge for the sample period [a] Unless otherwise approved, the sample shall be collected at the tap in the recirculation line. (sample period is 30 days). Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

There shall be no discharge of floating solids or visible foam in other than trace amounts. 2

- 1. Technology (e.g., Federal Effluent Guidelines)
- 2. Water Quality Standards (9 VAC 25-260 et. seq.) 3. Best Professional Judgment
 - Best Professional Judgment

OUTFALL # 206

Sewage treatment plant Outfall Description:

SIC CODE: 4911

To: Expiration From: Issuance () Interim Limits Effective Dates -(x) Final Limits

			EFELUI	EFELUENT LIMITATIONS	TIONS	MONITORING REQUIREMENTS	AING MENTS
PARAMETER & UNITS	BASIS FOR LIMITS	MULTIPLIER OR PRODUCTION	MONTHLY	MINIMUM	MAXIMUM	FREQUENCY	SAMPLE TYPE
Flow (MGD)	e		NA	NA	NL	1/Month	Est
Total Residual Chlorine (mg/l)[a]	8		NA	1.5	NA	1/Month	Grab
Enterococci (N/100ml) [a]	က		NA	NA	NL	1/Month	Grab

NA = NOT APPLICABLE; NL = NO LIMIT, MONITORING REQUIREMENT ONLY

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

- [a] See Part I.C. for Alternative Disinfection and Enterococci Monitoring.
- There shall be no discharge of floating solids or visible foam in other than trace amounts. 2

- 1. Technology (e.g., Federal Effluent Guidelines)
 2. Water Quality Standards (9 VAC 25-260 et. seq.)
 3. Best Professional Indoment

OUTFALL # 003

Outfall Description: Regulated storm water from coal pile runoff, bermed bulk storage fuel area runoff (301), combustion turbine area runoff, synfuel wash water runoff overflow, coal dock storm water and wash water

overflow SIC CODE: 4911

O Timito

(x) Final Limits () Inte	Interim Limits	s Effective Dates	- From: Is:	Issuance	To: Expiration	tion	
			EFFLUE	EFFLUENT LIMITATIONS	LONS	MONITORING REQUIREMENTS [a]	ING TS [a]
PARAMETER & UNITS	BASIS FOR LIMITS	MULTIPLIER OR PRODUCTION	MONTHLY AVERAGE	MINIMIM	MAXIMUM	FREQUENCY	SAMPLE TYPE [b]
Flow (MGD)	m		NA	NA	NL	1/6 Months	Est
рн (s.u.)	rl		NA	6.0	9.0	1/6 Months	Grab
TSS (mg/l) [c]	1		NA	NA	50	1/6 Months	Grab
TPH (mg/1) [d] [e]	m		NA	NA	NE	1/6 Months	Grab
Dissolved Copper (ug/1) [d]	е		NA	NA	NL	1/6 Months	Grab
Dissolved Zinc (ug/l) [d]	m		NA	NA	NL	1/6 Months	Grab

NA = NOT APPLICABLE; NL = NO LIMIT, MONITORING REQUIREMENT ONLY

1/6 Months = In accordance with the following schedule: 1st half (January 1 - June 30); 2nd half (July 1 December 31). Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR. the frequency required by the permit regardless of whether an actual discharge occurs.

[a] See Part I.F.1. for sampling methodology and reporting requirements.

- ൯ [b] The grab sample shall be taken within the first hour but not later than 24 hours of the start of discharge.
 - [c] See Part I.D.12. for overflow of untreated coal pile runoff from a 10-Year/24-Hour Storm.
- [e] TPH is the sum of individual gasoline range organics and diesel range organics or TPH-GRO and TPH-DRO to be measured by EPA SW 846 Method 8015C (2007) for gasoline and diesel range organics, or by EPA SW 846 Methods 8260B (1996) and 8270D (2007). If the combination of Methods 8260B and 8270D is used, the lab must report the total of gasoline range organics, diesel range organics and polynuclear aromatic hydrocarbons [d] See Parts I.D.5. and I.D. 6. For quantification levels and reporting requirements.
- 2. There shall be no discharge of floating solids or visible foam in other than trace amounts

- 1. Technology (e.g., Federal Effluent Guidelines)
- 2. Water Quality Standards (9 VAC 25-260 et. seq.) 3. Best Professional Judgment

- INDUSTRIAL EFFLUENT LIMITATIONS/MONITORING TABLE II

OUTFALL # 301

Storm water from bermed bulk oil storage area Outfall Description:

SIC CODE: 4911

SAMPLE TYPE Grab Grab REQUIREMENTS MONITORING FREQUENCY Months Months 1/3 1/3 To: Expiration MAXIMUM NL 30 EFFLUENT LIMITATIONS MINIMUM NA NA From: Issuance AVERAGE MONTHLY NA Ä I Effective Dates MULTIFLIER PRODUCTION () Interim Limits LIMITS BASIS FOR ന ന Q PARAMETER & UNITS (x) Final Limits TPH (mg/l) [a] Flow (MG)

= NO LIMIT, MONITORING REQUIREMENT ONLY NA = NOT APPLICABLE; NL 1/3 Months = In accordance with the following schedule: 1st quarter (January 1 - March 31); 2nd quarter (April 1 - June 30); 3rd quarter (July 1 - September 30); 4th quarter (October 1 - December 31)

ά L Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

TPH-GRO and TPH-DRO to organics, or by EPA SW 846 Methods 8260B (1996) and 8270D (2007). If the combination of Methods 8260B and [a] See Parts I.D.5. and I.D.6. for quantification levels and reporting requirements, respectively. 8270D is used, the lab must report the total of gasoline range organics, diesel range organics and [b] TPH is the sum of individual gasoline range organics and diesel range organics or be measured by EPA SW 846 Method 8015C (2007) for gasoline and diesel range

No discharge of tank bottom waters.

polynuclear aromatic hydrocarbons.

2. There shall be no discharge of floating solids or visible foam in other than trace amounts

- 1. Technology (e.g., Federal Effluent Guidelines)
- 2. Water Quality Standards (9 VAC 25-260 et. seq.) 3. Best Professional Judgment

OUTFALL # 004 and 005 (screen backwash units); 007, 008, and 009 (river recirculation.pits); 019 and 020 (fish return lines)

Outfall Description: Discharge of unaltered waters as they are drawn from the source supply SIC CODE: 4911

To: Expiration From: Issuance Effective Dates -() Interim Limits (x) Final Limits THESE DISCHARGES SHALL ONLY CONTAIN RIVER WATER FROM THE SCREEN BACKWASH UNITS, RIVER RECIRCULATION PITS AND FISH RETURN LINES. NO PROCESS WATER SHALL BE DISCHARGED FROM THESE OUTFALLS. NO MONITORING IS REQUIRED

INDUSTRIAL EFFLUENT LIMITATIONS/MONITORING ı TABLE II

OUTFALL # 010

Storm water from areas surrounding ash silos and truck wash Outfall Description:

SIC CODE: 4911

(x) Final Limits () Interim Limits	n Limits	Effective Dates -	From: Is	Issuance	To: Exp	To: Expiration	
			EFFLU	EFFLUENT LIMITATIONS	TIONS	MONITORING REQUIREMENTS	RING NTS [a]
PARAMETER & UNILS	BASIS FOR LIMITS	MULTIPLIER OR PRODUCTION	MONTHLY AVERAGE	MUMINIM	MAXIMUM	FREQUENCY	SAMPLE TYPE [d]
Flow (MG)	m		NA	NA	N	1/6 Months	Est [c]
ph (s.u.)	т		NA	NL	NL	1/6 Months	Grab
TSS (mg/l) [b]	3		NA	NA	NL	1/6 Months	Grab
TPH (mg/l) [b] [e]	ĸ		NA	NA	NT	1/6 Months	Grab
Dissolved Copper (ug/1) [b]	8		NA	NA	NĽ	1/Year	Grab
Dissolved Arsenic (ug/1) [b]	8		NA	NA	ΊN	1/Year	Grab
Dissolved Lead (ug/1) [b]	3		NA	NA	NL	1/Year	Grab
Dissolved Zinc (ug/1) [b]	က		NA	NA	NL	1/Year	Grab

NA = NOT APPLICABLE; NL = NO LIMIT, MONITORING REQUIREMENT ONLY

١ 1/6 Months = In accordance with the following schedule: 1st half (January 1 - June 30); 2nd half (July 1 December 31).

1/Year = Between January 1 and December 31.

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR. the frequency required by the permit regardless of whether an actual discharge occurs.

[a] See Part I.D.5. and I.D.6. for quantification levels and reporting requirements, respectively.

- Estimate of the total volume of the discharge during the storm event.
- [e] TPH is the sum of individual gasoline range organics and diesel range organics or TPH-GRO and TPH-DRO to be measured by EPA SW 846 Method 8015C (2007) for gasoline and diesel range organics, or by EPA SW 846 Methods 8260B (1996) and 8270D (2007). If the combination of Methods 8260B and 8270D is used, the lab must report the total of gasoline range organics, diesel range organics and polynuclear aromatic hydrocarbons. [d] The grab samples shall be taken within the first hour but not later than 24 hours of the discharge.
- 2. There shall be no discharge of floating solids or visible foam in other than trace amounts.

- 1. Technology (e.g., Federal Effluent Guidelines)
- 2. Water Quality Standards (9 VAC 25-260 et. seq.) 3. Best Professional Judgment

TABLE II - STORM WATER EFFLUENT LIMITATIONS/MONITORING

OUTFALL # 011 and 012

Outfall Description: Regulated storm water runoff from industrial activity areas including the loop track area and fuel oil storage area SIC CODE: 4911

NOTE: These outfalls represent storm event monitoring for existing

process and/or non-process outfalls.

PARAMETER & UNITS	STORM	Catalogue en escaposación esta actividade	HARGE ATIONS	MONITO REQUIREME	
	CATEGORY 1-29* or BPJ	MINIMUM	MUMIXAM	FREQUENCY	SAMPLE TYPE [c]
Flow (MG)	14	NA	NL	1/Year	Estima te [b]
pH (S.U.)	14	NL	NL	1/Year	Grab
TSS (mg/l) [d]	14	NA	NL	1/Year	Grab
TPH (mg/l)[d][e]	ВРЈ	NA	NL	1/Year	Grab
Dissolved Copper (ug/l) [d]	14	NA	NL	1/Year	Grab
Dissolved Zinc (ug/l) [d]	14	NA	NL	1/Year	Grab

1/Year = Between January 1 and December 31.

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

- [a] See Part I.F.1. for sampling methodology and reporting requirements.
- [b] Estimate of the total volume of the discharge during the storm event.
- [c] The grab sample shall be taken within the first hour but not later than 24 hours of the discharge.
- [d] See Parts I.D.5. and I.D.6. for quantification levels and reporting requirements, respectively.
- [e] TPH is the sum of individual gasoline range organics and diesel range organics or TPH-GRO and $\,$ TPH-DRO to be measured by EPA SW 846 Method 8015C (2007) for gasoline and diesel range organics, or by EPA SW 846 Methods 8260B (1996) and 8270D (2007). If the combination of Methods

8260B and 8270D is used, the lab must report the total of gasoline range organics, diesel range organics and polynuclear aromatic hydrocarbons.

There shall be no discharge of tank bottom waters.

2. There shall be no discharge of floating solids or visible foam in other than trace amounts.

The basis for the limitations codes are:

- A. Technology (e.g., Federal Effluent Guidelines)
- B. Water Quality Standards (9 VAC 25-260 et. seq.)
- C. Best Professional Judgment

*STORM REGS.-- CATEGORIES THAT REQUIRE MONITORING: [PICK AS APPROPRIATE]

- (1) Timber Products
- (2) Paper & Allied Products
- (3) Chemical & Allied Products
- (4) Asphalt Paving/Roofing Materials & Lubricant
- (5) Glass, Clay, Cement, Concrete & Gypsum Products
- (6) Primary Metals
- (7) Metal Mining (Ore Mining & Dressing)
- (8) Coal Mines & Coal Mining Related
- (9) Oil & Gas Extraction &
 Petroleum

Refineries

- (10) Hazardous Waste Treatment, Storage, Disposal
- (11) Landfills, Land Application Sites

& Open Dumps

- (12) Automobile Salvage Yards
- (13) Scrap/Waste Recycling
- (14) Steam Electric Power
 Generating, Inc. Coal
 Handling Areas

- (15) Motor Freight, Passenger,
 Rail, U.S. Postal
 Transportation & Petroleum
 Bulk Oil Stations and
 Terminals
- (16) Water Transportation With
 Maintenance and/or
 Equipment Cleaning
- (17) Ship/Boat Building or Repairing
- (18) Vehicle Maintenance,
 Equipment Cleaning or
 Deicing Areas At Air
 Transportation Facilities
- (19) Treatment Works
- (20) Food & Kindred Products
- (21) Textile Mills, Apparel & Other Fabric Products Mfg.
- (22) Wood & Metal Furniture and Fixture Mfg.

- (23) Printing & Publishing
- (24) Rubber, Miscellaneous Plastic Products & Miscellaneous Mfq.
- (25) Leather Tanning &

Finishing

- (26) Fabricated Metal Products
- (27) Transportation Equipment, Industrial or Commercial Machinery Mfg.
- (28) Electronic & Electrical
 Equipment and
 Components, Photographic
 & Optical Goods Mfg.
- (29) Nonclassified Facilities

OUTFALL # 013, 015, 018 and 021

Outfall Description: Storm water not associated with a regulated industrial activity SIC CODE: 4911

To: Expiration From: Issuance () Interim Limits Effective Dates -(x) Final Limits

THESE OUTFALLS SHALL ONLY CONTAIN STORM WATER NOT ASSOCIATED WITH A REGULATED INDUSTRIAL ACTIVITY NO PROCESS WATER SHALL BE DISCHARGED FROM THESE OUTFALLS. WHERE NO MONITORING IS REQUIRED.

2. There shall be no discharge of floating solids or visible foam in other than trace amounts.

TABLE II - STORM WATER EFFLUENT LIMITATIONS/MONITORING

OUTFALL # 016 and 017

Outfall Description: Regulated storm water runoff from an industrial

activity area SIC CODE: 4911

NOTE: These outfalls represent storm event monitoring for existing

process and/or non-process outfalls.

process and, or non	process cacre	xxx0.			
PARAMETER & UNITS	STORM		HARGE ATIONS	MONITO REQUIREME	elikka eliku sa katanan katanan (h. 1777).
	CATEGORY 1-29* or BPJ	MINIMUM	MAXIMUM	FREQUENCY	SAMPLE TYPE [c]
Flow (MG)	14	NA	NL	1/3 Months	Estima te [b]
рН (S.U.)	14	NL	NL	1/Year	Grab
TSS (mg/l)[d]	14	NA	NL	1/Year	Grab
TPH (mg/l)[d][e]	ВРЈ	NA	NL	1/Year	Grab
Dissolved Copper (ug/l) [d]	14	NA	NL	1/Year	Grab
Dissolved Zinc (ug/l) [d] [f]	14	NA	NL	1/3 Months	Grab

1/3 Months = In accordance with the following schedule: 1st quarter (January 1 - March 31); 2nd quarter (April 1 - June 30); 3rd quarter (July 1 - September 30); 4th quarter (October 1 - December 31). 1/Year = Between January 1 and December 31.

These outfalls are considered substantially identical; 016 may be sampled for 017; sample results shall be reported for both outfalls.

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

- [a] See Part I.F.1. for sampling methodology and reporting requirements.
- [b] Estimate of the total volume of the discharge during the storm event.
- [c] The grab sample shall be taken within the first hour but not later than 24 hours of the discharge.
- [d] See Parts I.D.5. and I.D6. for quantification levels and reporting requirements, respectively.

[e] TPH is the sum of individual gasoline range organics and diesel range organics or TPH-GRO and TPH-DRO to be measured by EPA SW 846 Method 8015C (2007) for gasoline and diesel range organics, or by EPA SW 846 Methods 8260B (1996) and 8270D (2007). If the combination of Methods 8260B and 8270D is used, the lab must report the total of gasoline range organics, diesel range organics and polynuclear aromatic hydrocarbons. [f] See Part I.F. for Storm Water Evaluation requirements.

The basis for the limitations codes are:

- A. Technology (e.g., Federal Effluent Guidelines)
- B. Water Quality Standards (9 VAC 25-260 et. seq.)
- C. Best Professional Judgment

*STORM REGS. -- CATEGORIES THAT REQUIRE MONITORING:

- (1) Timber Products
- (2) Paper & Allied Products
- (5) Chemical & Allied Products
- (6) Asphalt Paving/Roofing
 Materials & Lubricant
- (6) Glass, Clay, Cement, Concrete & Gypsum Products
- (6) Primary Metals
- (8) Coal Mines & Coal Mining Related
- (9) Oil & Gas Extraction &
 Petroleum

Refineries

- (10) Hazardous Waste Treatment, Storage, Disposal
- (11) Landfills, Land Application Sites
 - & Open Dumps
- (12) Automobile Salvage Yards
- (13) Scrap/Waste Recycling
- (14) Steam Electric Power Generating, Inc. Coal Handling Areas

- (15) Motor Freight, Passenger,
 Rail, U.S. Postal
 Transportation & Petroleum
 Bulk Oil Stations and
 Terminals
- (16) Water Transportation With Maintenance and/or Equipment Cleaning
- (17) Ship/Boat Building or Repairing
- (18) Vehicle Maintenance, Equipment Cleaning or Deicing Areas At Air Transportation Facilities
- (19) Treatment Works
- (20) Food & Kindred Products
- (21) Textile Mills, Apparel &
 Other Fabric Products Mfg.
- (22) Wood & Metal Furniture and Fixture Mfg.

- (23) Printing & Publishing
- (24) Rubber, Miscellaneous Plastic Products & Miscellaneous Mfg.
- (25) Leather Tanning & Finishing
- (26) Fabricated Metal Products
- (27) Transportation Equipment, Industrial or Commercial Machinery Mfg.
- (28) Electronic & Electrical
 Equipment and
 Components, Photographic
 & Optical Goods Mfq.
- (29) Nonclassified Facilities

TABLE II - STORM WATER EFFLUENT LIMITATIONS/MONITORING

OUTFALL # 030

Outfall Description: Regulated storm water runoff from an industrial activity area - coal unloading dock after the first 1.0 inches of

precipitation is collected for treatment

SIC CODE: 4911

NOTE: These outfalls represent storm event monitoring for existing

process and/or non-process outfalls.

PARAMETER & UNITS	STORM	DISCHARGE LIMITATIONS		MONITORING REQUIREMENTS [a]	
	CATEGORY 1-29 or BPJ	MINIMUM	MUMIXAM	FREQUENCY	SAMPLE TYPE [c]
Flow (MG)	14	NA	NL	1/6 Months	Estima te [b]
pH (S.U.)	14	NL	NL	1/6 Months	Grab
TSS (mg/l) [d]	14	NA	NL	1/6 Months	Grab
TPH (mg/l)[d][e]	ВРЈ	NA	NL	1/6 Months	Grab

1/6 Months = In accordance with the following schedule: 1st half (January 1 - June 30); 2nd half (July 1 - December 31).

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

- [a] See Part I.F.1. for sampling methodology and reporting requirements.
- [b] Estimate of the total volume of the discharge during the storm event.
- [c] The grab sample shall be taken within the first hour but not later than 24 hours of the discharge.
- [d] See Parts I.D.5 and I.D.6 for quantification levels and reporting requirements.
- [e] TPH is the sum of individual gasoline range organics and diesel range organics or TPH-GRO and TPH-DRO to be measured by EPA SW 846 Method 8015C (2007) for gasoline and diesel range organics, or by EPA SW 846 Methods 8260B (1996) and 8270D (2007). If the combination of Methods 8260B and 8270D is used, the lab must report the total of gasoline range organics, diesel range organics and polynuclear aromatic hydrocarbons.

The basis for the limitations codes are:

- A. Technology (e.g., Federal Effluent Guidelines)
- B. Water Quality Standards (9 VAC 25-260 et. seq.)
- C. Best Professional Judgment

*STORM REGS.-- CATEGORIES THAT REQUIRE MONITORING:

- (1) Timber Products
- (2) Paper & Allied Products
- (7) Chemical & Allied Products
- (8) Asphalt Paving/Roofing
 Materials & Lubricant
- (7) Glass, Clay, Cement, Concrete & Gypsum Products
- (6) Primary Metals
- (8) Coal Mines & Coal Mining Related
- (9) Oil & Gas Extraction & Petroleum

Refineries

- (10) Hazardous Waste Treatment, Storage, Disposal
- (11) Landfills, Land Application Sites
 - & Open Dumps
- (12) Automobile Salvage Yards
- (13) Scrap/Waste Recycling
- (14) Steam Electric Power Generating, Inc. Coal Handling Areas

- (15) Motor Freight, Passenger,
 Rail, U.S. Postal
 Transportation & Petroleum
 Bulk Oil Stations and
 Terminals
- (16) Water Transportation With Maintenance and/or Equipment Cleaning
- (17) Ship/Boat Building or Repairing
- (18) Vehicle Maintenance,
 Equipment Cleaning or
 Deicing Areas At Air
 Transportation Facilities
- (19) Treatment Works
- (20) Food & Kindred Products
- (21) Textile Mills, Apparel & Other Fabric Products Mfg.
- (22) Wood & Metal Furniture and Fixture Mfg.

- (23) Printing & Publishing
- (24) Rubber, Miscellaneous Plastic Products & Miscellaneous Mfg.
- (25) Leather Tanning & Finishing
- (26) Fabricated Metal Products
- (27) Transportation Equipment, Industrial or Commercial Machinery Mfg.
- (28) Electronic & Electrical
 Equipment and
 Components, Photographic
 & Optical Goods Mfg.
- (29) Nonclassified Facilities

- INDUSTRIAL EFFLUENT LIMITATIONS/MONITORING TABLE II

OUTFALL # 031

Outfall Description: Uncontaminated river water from the chlorination building SIC CODE: 4911

(x) Final Limits () Interim Limits) Interim Limits	Effective Dates -	From: Issuance	ance	To: Expiration	ation	
			DTLA	EFFLUENT LIMITATIONS	SNOTE	MONITORING REQUIREMENTS	RING MENTS
PARAMETER & UNITS	BASIS FOR LIMITS	MULTIPLIER OR PRODUCTION	MONTHLY	MINIMOM	MAXIMUM	FREQUENCY	SAMPLE TYPE
Flow (MGD).			NA	NA	NL	1/6 Months	Est
pH (S.U.)			NA	NL	NE	1/6 Months	Grab
Total Residual Chlorine (uq/1) [a]	i.		NA	NA	Z	1/6 Months	Grab

NA = NOT APPLICABLE; NL = NO LIMIT, MONITORING REQUIREMENT ONLY

ı - June 30); 2nd half (July 1 1st half (January 1 1/6 Months = In accordance with the following schedule: December 31).

1/Year = Between January 1 and December 31.

Upon issuance of the permit, Discharge Monitoring Reports (DMRs) shall be submitted to the regional office at the frequency required by the permit regardless of whether an actual discharge occurs. In the event that there is no discharge for the monitoring period, then "no discharge" shall be reported on the DMR.

- [a] See Parts I.D.5. and I.D.6. for quantification levels and reporting requirements, respectively.
- There shall be no discharge of floating solids or visible foam in other than trace amounts 2
- There shall be no discharge from strainer cleaning to this outfall . ص

- 1. Technology (e.g., Federal Effluent Guidelines) 2. Water Quality Standards (9 VAC 25-260 et. seq.) 3. Best Professional Judgment